



WWW.BEAUROC.COM



STAINLESS STEEL BODY LINE

PRODUCT CATALOGUE

STAINLESS STEEL

BODY LINE



SSM1/SSM4 | Quality SS201 & SS304 designs for the municipal market

BODY OPTIONS

TOP RAIL	7g (3/16") – SS201/SS304 2B (one piece with dirt shedding)	10g (1/8") – SS201/SS304 2B (one piece with dirt shedding)	MATERIALS
SIDES	7g (3/16") – SS201/SS304 2B	10g (1/8") – SS201/SS304 2B	
SIDE POSTS	NONE	10g (1/8") – SS201/SS304 2B	
FRONT	7g (3/16") – SS201/SS304 2B	10g (1/8") – SS201/SS304 2B	
TAILGATE	7g (3/16") – SS201/SS304 2B	3-panel or 6-panel design	
FLOOR	4.5 mm (3/16") – HARDOX 450	7g (3/16") – SS201/SS304 2B / 1/4" – HARDOX 450	
SILLS	3/16" Domex 100W	7g (3/16") – SS201/SS304 2B	
BODY WEIGHT	2877 lbs Based on a 10' x 30" x 36" SSM4		SPECIFICATIONS
STANDARD BODY LENGTHS	8' 6" to 17' 0"	—	
STANDARD SIDE HEIGHTS	24", 30", 36", 42", 48"	—	
STANDARD TAILGATE HEIGHTS	30", 36", 42", 48", 54"	—	
STANDARD FRONT HEIGHT	86" to 88" trapezoidal design	—	
STANDARD HOIST SYSTEM	Front Mount Telescopic	Underbody Hoist	

SSM1/SSM4 Available Options:

- Coal doors
- Double-acting tailgate
- Asphalt tail
- 10" long sills
- Hook-lift frame
- Tapered sides
- Tarp rails
- Underbody Hoist System

MATERIALS LEGEND: TENSILE STRENGTH BY GRADE OF STEEL MEASURED IN PSI

HARDOX 450 – 215,000

Domex 100W – 115,000*

SS201 2B – 95,000

SS304 2B – 74,700

*Weather resistant steel.



300 Universelle street
Vars, Ontario, Canada K0A 3H0
Tel: 613.443.0044 – Fax: 613.443.1138