

DIAMOND

ELLIPTICAL BODY LINE



THE BODIES SHOWN MAY HAVE DEALER INSTALLED OPTIONS.

RXL | A versatile body for all your heavy duty applications

RXH | An ideal choice for all your super duty needs

TOP RAIL	4" x 4" x 3/16" tubing	4" x 4" x 1/4" tubing
SIDES	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
SIDE POSTS	NONE	NONE
FRONT	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
TAILGATE	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
FLOOR	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
SILLS	1/4" – 44-W	1/4" – 44-W
BODY WEIGHT	5,118 lbs Based on a 17'6" x 54" x 60" RXL	6,080 lbs Based on a 17'6" x 54" x 60" RXH
STANDARD BODY LENGTHS	10' to 20'	10' to 20'
STANDARD SIDE HEIGHTS	36" to 66"	36" to 66"
STANDARD TAILGATE HEIGHTS	36" to 72"	36" to 72"
STANDARD INSIDE WIDTH	88"	88"
STANDARD HOIST SYSTEM	Front Mount Telescopic	Front Mount Telescopic
OPTIONAL HOIST SYSTEM	Underbody Hoist	Underbody Hoist

MATERIALS

SPECIFICATIONS

ONLY BEAU-ROC DELIVERS “THE DIAMOND STANDARD”



- Responsive custom design with efficient, on-time delivery from modern 60,000 sq. ft. facility
- Maximum productivity with the original Diamond sidewall profile
- More years and more miles of service with HARDOX 450 steel
- Lowest total operating cost for the life of your truck

A ROCK SOLID INVESTMENT

- **More pay per load:** No posts and braces means less weight without losing cubic capacity
- **100% HARDOX 450 steel body:** Proven wear-resistance for best in industry durability
- **Save on every mile:** Up to 7% fuel savings
- **Less wear, fewer repairs:** Diamond profile flexes instead of breaking under normal stresses
- **Quicker clean-outs:** One-piece tapered floor eliminates catch points for loads
- **Faster delivery:** Fewer weld points save time in production
- **The best look for your business:** Clean, smooth sidewalls for signage and decals

NEED A QUOTE NOW?

Our detailed product database allows us to configure your order in real time. We provide custom quotations to our dealers quickly, then follow through with a seamless flow of production details for manufacturing.



300 Universelle Street
Vars, Ontario, Canada K0A 3H0
Tel: 613.443.0044 – Fax: 613.443.1138

