



[WWW.BEAUROC.COM](http://WWW.BEAUROC.COM)



# MULTI-PURPOSE BODY LINE

PRODUCT CATALOGUE



**MPLD**

Multi-Purpose Light Duty  
Municipality & Landscaping



**MPHD**

Multi-Purpose Heavy Duty  
All Purpose Body for Rip-Rap, Debris,  
Scrap Steel Hauling & Demolition



Multi-Purpose Medium Duty  
Municipality & Landscaping

# MPMD



Multi-Purpose Chipper Body  
Municipality, Landscaping Utility Work & Tree Service

# CHIPPER



## MPLD

## MPMD

## MPHDO\*

## CCS

## CCL

MATERIALS	MPLD	MPMD	MPHDO*	CCS	CCL
TOP RAIL	3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing	4" x 4" x 1/4" tubing	Not applicable	Not applicable
SIDES	10g (0.134") – A-36	3/16" – Domex 100W	4.5 mm (3/16") – HARDOX 450	10g (0.134") – A-36	10g (0.134") – A-36
FRONT	10g (0.134") – A-36	3/16" – Domex 100W	4.5 mm (3/16") – HARDOX 450	10g (0.134") – A-36	10g (0.134") – A-36
TAILGATE	12g (0.1046") – A-36	11g (0.1196") – Domex 100W	4 mm (5/32") – HARDOX 450	11g (0.1196") – Domex 100W	12g (0.1046") – A-36
FLOOR	3/16" – 44-W	3/16" – Domex 100W	1/4" – HARDOX 450	10g (0.134") – A-36	10g (0.134") – A-36
SILLS	8" C-channel with support flange	8" C-channel with support flange	8" I-beam with support flange	8" formed or channel long sills – 3/16" 44W	8" formed or channel long sills – 3/16" 44W
BODY WEIGHT	2,845 lbs Based on a 12' x 48" x 16" MPLD	3,500 lbs Based on a 15' x 48" x 32" MPMD	8,950 lbs Based on a 23' x 60" x 96" MPHDO	4,260 lbs Based on a 14' x 84" x 32" CCS	3,880 lbs Based on a 14' x 80" x 20" CCL
STANDARD INSIDE WIDTH	87"	87"	86"–88" trapezoidal design	94"	94"
STANDARD BODY LENGTHS	10' to 18'	10' to 18'	15' to 30'	10' to 18'	10' to 18'
STANDARD SIDE HEIGHTS	48", 54" & 60"	48", 54" & 60"	60", 66", 72", 84" & 96"	60", 72", 84"	60", 72", 84"
STANDARD TAILGATE HEIGHTS	16", 32", 48", 54" & 60"	16", 32", 48", 54" & 60"	60", 66", 72", 84" & 96"	20" & 32"	20" & 32"
STANDARD FRONT HEIGHTS	Same as side height	Same as side height	48" & 60"	Same as side height	Same as side height
STANDARD HOIST SYSTEM	Underbody hoist	Underbody hoist	Front mount telescopic	Front mount & underbody hoist	Front mount & underbody hoist

## SPECIFICATIONS

Underbody hoist

Underbody hoist

Front mount telescopic

Front mount & underbody hoist

Front mount & underbody hoist

## MPLD & MPMD Options:

- Side door: 10g (0.134") A-36 with 3" x 4" x 3/16" tubing x 52" wide
- Double barn (swing) tailgate
- Upper split mesh barn door (available with 16" double acting tailgate only)
- Removable roof top (2 sections)

## Chipper Body Options:

- Removable top model – CCL-RT (60" side height only)
- Ladder insert (available on both CCS & CCL models)
- Double barn door (available on both CCS & CCL models)

## \* Non-Dumping Model Available (MPHDO)

Grapple hooks shown with MPMD & MPHDO are dealer installed systems

## MATERIALS LEGEND:

A-36 – 65,000 psi	44W – 80,000 psi
Domex 100W – 115,000 psi *	HARDOX 450 – 215,000 psi
*Weather resistant steel	psi value = typical tensile



300 Universelle Street  
 Vars, Ontario, Canada K0A 3H0  
 Tel: 613.443.0044 – Fax: 613.443.1138